Mobil

Mobil™ Garden Oil 4T

Mobil Passenger Vehicle Lube , Germany

Engine Oil

Product Description

Mobil™ Garden Oil 4T is a multigrade SAE 10W-30 engine oil designed for 4-stroke garden machines.

Features and Benefits

Mobil Garden Oil 4T 10W-30 combines highly refined, quality mineral oils and balanced additive system to provide following benefits:

- Low oil consumption
- Keeps engine clean
- Protects engine in hot conditions
- Good protection against corrosion

Applications

- Garden machines with 4-stroke engine like lawn mowers, rototillers, chaff cutters etc.
- Manufacturer's recommendations for oil drain and filter change intervals should be followed

Specifications and Approvals

This product is recommended for use in applications requiring:	
API SG	
API SH	
API CF-4	

This product meets or exceeds the requirements of:	
API SJ	

Properties and Specifications

Property	
Grade	SAE 10W-30
Ash, Sulfated, mass%, ASTM D874	1.1
Flash Point, Cleveland Open Cup, °C, ASTM D92	225
Viscosity Index, ASTM D2270	141

Mobil™ Garden Oil 4T

Property	
Pour Point, °C, ASTM D97	-36
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	79.5
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	11.7

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims /psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2021

EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL, BVBA (EMPC) POLDERDIJKWEG B-2030 Antwerpen Belgium

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: https://www.mobil.com.de/de-de/kontakt

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

