

## Description

ACEA C4 and C3 quality synthetic lubricant oil, specially recommended in vehicles with particle filters and exhaust fume treatment. It stands out for its low ash formation (Low SAPS), and it is most adequate for Renault diesel vehicles that require RN0720 quality level. It is also a long-lasting lubricant, allowing significant extension of oil change intervals; always according to the manufacturers recommendations,

## Properties

- Its reduced ash content (Low SAPS) makes it essential for ensuring the durability of new technologies applied to reduce pollutant emission levels, such as diesel particle filters (DPF).
- The RN0720 quality level ensures high oil resistance to oxidation and a minimum formation of deposits in the piston, thus extending the oil change period.
- Contributes to reducing CO2 emissions, obtaining fuel savings of up to 1 % compared to other lubricants under standard M111FE test conditions.

## Quality levels, approvals and recommendations

- ACEA C4 y C3
- RENAULT RN0720\*
- MB229.51/226.51\*

\*Formal approval

## Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			5W-30
Density at 15 °C	g/mL	ASTM D 4052	0,854
Viscosity at 100 °C	cSt	ASTM D 445	12,2
Viscosity at 40 °C	cSt	ASTM D 445	70
Viscosity at -30 °C	cP	ASTM D 5293	6600 max.
Viscosity index	-	ASTM D 2270	173
Flash point, open cup	°C	ASTM D 92	200 min.
Pour point	°C	ASTM D 97	-33 max.
T.B.N.	mg KOH/g	ASTM D 2896	6,6

The above mentioned characteristics are typical values and should not be considered product specifications.