



MANNOL ATF-A PSF 8203

Universal all-season mineral oil for power steering systems, automatic transmissions of older generations, torque converters and hydraulic clutches of all types of vehicles. Designed following GM requirements.

Product properties:

- Can be used all year round, even in frigid environments due to very low pour point (-45 °C and below);
- Maintains stable viscosity and fluidity even at low temperatures due to a stable viscosity index. Functionality is not dependent on the operating temperature, which ensures minimal power loss, high energy conversion efficiency and low maintenance costs;
- Compatible with all types of gaskets, seals and hoses;
- High thermal and antioxidant stability at high temperatures protects against the formation of deposits and reduces losses due to evaporation;
- Optimum frictional properties ensure smooth operation of the transmission and excellent longlasting synchronization even in harsh operating conditions;
- Effectively redirects heat generated by transmissions to the car body or the cooling system;
- Protects against corrosion, wear and effectively resists foaming.

Designed for use as a hydraulic and power transmission fluid for cars and trucks, buses and other special vehicles in accordance with the GM ATF-A Suffix specification A.

Specifications

ALLISON C3
CATERPILLAR TO-2
GM ATF Type A Suffix A

Approval

Recommendation

PACKAGING

4L	MN8203-4	Plastic	4 pcs/box
1000L	MN8203-IBC	Pallet tank	
208L	MN8203-DR	Drum	
60L	MN8203-60	Drum	
20L	MN8203-20	Plastic	
10L	MN8203-10	Plastic	
1L	MN8203-1	Plastic	20 pcs/box

