



Transmax DUAL

Dual Clutch Fluid

Description

Castrol Transmax DUAL, is a full synthetic SAE 75W dual clutch transmission fluid. This product is suitable for use in (6-speed) VW, Audi, Skoda and SEAT DSG.

Castrol Transmax DUAL, formulated with Smooth Drive Technology™, delivers enhanced protection and gives drivers a smoother drive for longer.

Application

Castrol Transmax DUAL is suitable for use in dual clutch transmissions in applicable Ford, Volvo, VW, Audi, Skoda and Mitsubishi vehicles.

Advantages

- Enhanced friction durability for smooth transmission performance
- Improved wear protection to provide longer component life
- Excellent thermal and oxidative stability to effectively resist oxidation
- Excellent synchroniser and clutch performance due to balanced frictional characteristics
- High shear resistance - constant viscosity during oil life
- Proven performance in field trials

Typical Characteristics

Name	Method	Units	Transmax DUAL
Colour	Visual	-	green
Density @ 15C	DIN EN ISO 12185	g/ml	0.838
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	7.2
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	35.5
Viscosity Index	DIN ISO 2909	None	166
Viscosity, Brookfield @ -40C (75W)	DIN 51398	mPa.s (cP)	7500
Pour Point	DIN-ISO 3016	°C	-72
Flash Point, COC	ASTM D92	°C	234

Product Performance Claims

Approved - Audi / VW TL 52529 (G 052 529)

Suitable for use in the following: Audi / VW TL 52182 (G 052 182), Seat Chrysler (Europe)

Ford WSS-M2C936-A (Dual Clutch)

Mitsubishi dual clutch including Dia Queen SSTF-1

Peugeot using Getrag DCT, PSA Transmission oil 9734 52

Skoda 6-speed Dual Clutch Transmission (DSG)

Volvo Dual Clutch Transmission

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Transmax DUAL

12 Aug 2021

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 132 McCredie Road, Guildford NSW 2161, Australia
Technical Advice Line 1300 557 998 Customer Service 1300 554 890
www.castrol.com.au www.msds.castrol.com.au