

## Q8 Rembrandt EP 2

Advanced lithium extreme pressure grease

### Description

Q8 Rembrandt EP 2 is a multi-purpose lithium grease with extreme pressure properties and is temperature resistant up to 130°C. The grease is based on mineral oil and has optimum pumpability thanks to its smooth structure. The advanced roll stability of the Q8 Rembrandt EP 2, the high anti-wear properties and rust protection lead to a long service life of the grease.

### Applications

Q8 Rembrandt EP 2 is used in industrial and automotive applications. Q8 Rembrandt EP 2 is highly recommended for highly loaded plain- and anti-friction bearings, bushings and pins in draglines, bulldozers, tractors, excavators, trucks, hoisting equipment, winches etc.

### Benefits

- Improves the durability of the equipment thanks to its characteristics
- Extreme pressure characteristics
- Advanced mechanical stability
- Highly appropriate for use in a wide range of temperatures
- Optimum anti-rust characteristics

### Specifications & Approvals

<b>DIN</b>	51502 KP2K-30	<b>ISO</b>	6743 L-XCCFB2
<b>Danieli</b>	Standard 0.000.001-R15 (2020)		

### Properties

	Method	Unit	Typical
Soap type	-	-	Lithium
Colour	Visual	-	Brown
Consistency, NLGI No.	NLGI	-	NLGI 2
Penetration, Worked, 25 °C, 60 strokes	D 217	0.1 mm	288
Kin. Viscosity Base Oil at 40 °C	D 445	mm <sup>2</sup> /s	190
Dropping Point	D 566	°C	205
Copper Corrosion, 100 °C, 24 h	D 4048	-	pass
Four Ball Test, Weld Load	IP 239	N	2450

The figures above are not a specification. They are typical figures obtained within production tolerances.