



Transmax Agri MP 15W-40

Universal tractor oil

Description

Castrol Transmax Agri MP 15W-40 is a universal API GL-4 oil for most types of farm machinery.

Advantages

- One oil that protects engine, transmission, wet brake, hydraulic and front axles
- One oil reduces inventory, saves money
- Using an advanced formulation, Castrol Agri MP reduces engine wear by up to 30% compared to conventional STOU products

Typical Characteristics

Name	Method	Units	Transmax Agri MP 15W-40
Density @ 15C, Relative	ASTM D1298	g/ml	0.880
Viscosity, Kinematic 100C	ASTM D445	mm²/s	13.4
Viscosity, Kinematic 40C	ASTM D445	mm²/s	93
Viscosity Index	ASTM D2270	None	144
Viscosity, CCS -20C	ASTM D5293	mPa.s (cP)	4500
Viscosity, Brookfield @ -18C	ASTM D2983	mPa.s (cP)	7300
Pour Point	ASTM D97	°C	-45
Flash Point, COC	ASTM D92	°C	230

Product Performance Claims

API CE/SF/GL-4 ZFTE-ML 06B*, 07B Meets - John Deere JDM J27, Massey Ferguson M1144, Sperry Vickers/Eaton M2950S Sperry Vickers/ Eaton I-280-S, Sauer Sunstrand/ Danfoss: Hydrostatic Trans Fluid Suitable for use where Case MAT 3525, Ford M2C134-D/ M2C86-B/ M2C159-B, John Deere JDM J20C, Massey Fergusson M1139 New Holland FNHA-2-C-201.00 FNH 82009202 NH 410B are specified

Additional Information

Transmax Agri MP 15W-40 is registered under the following ZF approval numbers: ZF002166, ZF002170, ZF002171, ZF002172

Transmax Agri MP 15W-40 02 Jun 2022 Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com