



Duratec MX

Gas Engine Lubricant

Description

Castrol Duratec MX is a mineral based zinc and phosphorus free SAE 40 medium ash gas engine lubricant.

Application

Duratec MX is for use in both spark ignition and dual-fuel gas engines. It is formulated specifically for use in four stroke medium and high speed engines running on aggressive landfill and sour gas fuels. The medium ash additive system provides protection against valve recession whilst still maintaining combustion space and turbocharger cleanliness. Duratec MX provides a high degree of engine protection against corrosion and wear which can result from the high concentrations of halogens and hydrogen sulphide frequently encountered in such applications. Duratec MX is approved by: Jenbacher - Series 2 & 3 gas engines: Landfill gas, digester gas, sewage gas applications (TA1000-1105 and TA 1000-0125). Deutz - Landfill gas, digester gas, sewage gas applications. Man Nutzfahrzeuge AG - Natural gas, landfill gas, sewage gas applications. Guascor

Advantages

- High resistance to oxidation and nitration leads to longer oil life and extends drain intervals. This reduces maintenance costs and down time.
- Excellent antiwear characteristics provide outstanding protection against piston and cylinder wear and scuffing.
- Efficient neutralisation of acidic combustion products from landfill gases provides outstanding resistance to acid corrosion
- Low combustion space and turbocharger deposit
- Longer service life in aggressive fuel gas applications.
- Low crankcase deposits and cleaner operation.

Characteristics

Test	Method	Units	Duratec MX
SAE Class			40
Density @ 15°C	ISO 12185 / ASTM D4052	g/ml	0.89
K.V. @ 100°C	ISO 3104 / ASTM D445	mm ² /s	13
K.V. @ 40°C	ISO 3104 / ASTM D445	mm ² /s	124
Viscosity Index	ISO 2909 / ASTM 2270	-	98
Pour Point	ISO 3016 / ASTM D97	°C	-18
Flash Point, COC	ISO 2592 / ASTM D92	°C	258
Flash Point, PMCC	ISO 2719 / ASTM D93	°C	215
TBN	ISO 3771 / ASTM D2896	mgKOH/g	7.2
Sulphated Ash	ISO 3987 / ASTM D874	% wt	0.7
Zinc	ASTM D4951	ppm	<10
Phosphorus	ASTM D4951	ppm	<10
Boron	ASTM D4951	ppm	150

Typical Characteristics

Name	Method	Units	

Duratec MX

04 Sep 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

Storage

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that the product is stored in accordance with the data sheet. The responsibility of the user to validate and use products should be stored above 60°C, exposed to hot sun or fire, and other conditions. All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of markings. Products should be stored in a cool, dry place, away from fire, and other conditions. Castrol (UK) Limited, PO BOX 352, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW. Orders/Enquiries: 0345 9645111 Technical Enquiries: 0345 082 1719 www.castrol.com/industrial

Castrol (UK) Limited, PO BOX 352, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW
Orders/Enquiries: 0345 9645111 Technical Enquiries: 0345 082 1719
www.castrol.com/industrial