

Certificate of conformity BDC

Hereby we declare that the formula of BDC got an upgrade with a new additive. Therefore, the products color looks different the previous formula.

New formula is used starting from LOT NR : 182887 – XXXXXX

The new updated BDC formula has the same properties as before :

- Lubricates and protects the injection system
- Prevents the formation of carbon deposits on valves and allows for a better spraying of fuel into the engine by cleaning the injector nozzles
- Reduces the harmful exhaust emissions
- Improves the cetane rate for a better combustion and a reduction of consumption
- Repels condensation water and therefore prevents the formation of bacteria which can provoke severe damage to the fuel pump
- Protects against corrosion (ASTM D665 test) and oxidation (ASTM D2774 test)
- Offers an antifreeze protection by lowering the Limit Filterability Temperature (LFT)

Instructions for use are unchanged :

- Summer use : 1L for 1000L of diesel
- Winter use : 2L for 1000L of diesel
- Caution : make sure you make the treatment when the outside temperature is superior to +5°C



Old version

New version

Sandrine Kokosinski
Laboratory Manager



SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers, 3 - Z.I. Tournai Ouest 2
7522 TOURNAI
Belgique
Tél. : +32(0)69 590 360 - Fax +32(0)69 590 361
R.C. Tournai num 89060 - Code NACE 2466
TVA BE 477 929 886