

LPG Valve Lube (LPG-VL)

LPG Valve Lube

Product properties

LPG Valve Lube is a high active fuel additive, reducing wear and tear of valves and valve seats of liquefied petroleum gas powered engines. The sensational product composition cleans and lubricates the upper area of the combustion chamber and forms a protective barrier between valve and valve seat. The high active protection against wear and tear and the optimized dissipation of heat dissipation provide for an improved cooling of valves and valve seats. Suitable for vehicles with catalytic converter.

Your benefits:

- permanent lubrication of valves, thereby long term protection of valves and valve seats
- optimized fuel consumption and reduced exhaust gas emission
- removes reliably and lasting the contamination of the combustion chamber
- ensures safe lubrication
- optimal protection against "valve impact"
- extended life span of the engine

Area of application

To use in automatic dispensers (e.g. Flashlube Lubrication System) of bivalent vehicles (gas/petrol powered)).

Application

PRO-TEC LPG Valve Lube is only for application in automatic dispensers of bivalent vehicles (gas/petrol powered). Apply the product at a regular base to the automatic dispenser.

Attention: strictly follow the corresponding instructions of the manufacturer.

Consumption

Automatic addition by the dispenser, approx. 50 ml sufficient for 50 litres fuel.

Reaction time

works during running

Technical data

Physical state: liquid

Colour: clear/colourless

Odour: characteristic

Initial boiling point and boiling range: 180 - 210 °C

Flashpoint: > 61 °C

Density at 68 °F: 0.790 - 0.83 g/cm³

Water resistant

viscosity at 68 °F (mm²/s): 1,91 mm²/s

Available sizes	Item no.	PU
500ml	P1991	24
1L	P1999	12
5L	P1992	4



Our information is based on careful examination and may be considered as reliable. However, all information supplied is non-binding advise. No liability for any printing errors. Technical modifications and errors are exempted.